

HF-BANDPLAN (based on BANDWIDTH) valid from 01-01-2003

BAND	Source		USAGE
	Frequency Segment (kHz)	Max. Bandwidth [Hz]	
160 m	1810 - 1838	200	cw
	1838 - 1840	500	all
	1840 - 1842	2700	all
	1842 - 2000	2700	phone,cw
80 m	3500 -3510	200	cw-dx
	3500 -3560	200	cw, contest preferred
	3560 - 3600	500	all
	3600 - 3650	2700	phone, contest preferred, all
	3650 - 3700	2700	phone,all+F61
	3700 - 3800	2700	phone, contest preferred,all
	3775 - 3800	2700	phone-dx, cw
40 m	7000 -7035	200	cw
	7035 - 7040	500	all
	7040 - 7045	2700	all
	7045 - 7100	2700	phone,cw
30 m	10100 - 10140	200	cw
	10140 - 10150	500	all
20 m	14000 - 14060	200	cw, contest preferred
	14060 - 14070	200	cw
	14070 - 14099	500	all
	14099 - 14101	200	IBP
	14101 - 14112	500	all
	14112 - 14125	2700	phone,cw
17 m	18068 - 18100	200	cw
	18100 - 18109	500	all
	18109 - 18111	200	IBP
	18111 - 18168	2700	phone, cw
15 m	21000 - 21080	200	cw
	21080 - 21120	500	all
	21120 - 21149	200	cw
	21149 -21151	200	IBP
	21151 - 21450	2700	phone, all
12 m	24890 - 24920	200	cw
	24920 - 24929	500	all
	24929 - 24931	200	IBP
	24931 - 24990	2700	phone, cw
10 m	28000 - 28050	200	cw
	28050 - 28150	500	all
	28150 - 28190	200	cw
	28190 - 28199	200	regional time shared IBP
	28199 - 28201	200	world wide time shared IBP
	28201 - 28225	200	continuous-duty IBP
	28225 - 29200	2700	phone, all
	29200 - 29300	6000	all
	29300 - 29510	6000	satellite down-link
29510 - 29700	6000	all	